VIRA CH K Series

Advanced Battery Charger

MODEL					1280
OUTPUT					
Battery Type	Load Acid / Li-ion / Gel / AGM				
Standard Boost Charge Voltage	14.4V / 14.7V (Select by S1-1)				
	15A	25A	35A	50A	80A
	0~15A	0~25A	0~35A	0~50A	0~80A
	3- stage charging capability (IUOU)				
	15A	25A	35A	40A	40A
	~				
	~				
Efficiency (Typ.) at 230VAC					
	17.5V ± 1% Protection type: Shut dpwn output (recovery after resetting AC power on)				
	°				
	°				
	Protection type: Auto recovery after heat sink temperature goes down to 50°C				
Alarm Signal	NC . / NO. Relay contact output (Please refer to page 5 Alarms Signal & Fan Contral)				
	Supply 13.2V Current limit output voltage				
	-10mV / 0.5°C with COTED temperature sensor				
	By Romate Controller and S1-4 DIP switch (please refer to page 4~5)				
	Support COTEK Remote Controller CR-1 setting Function (CN3 or CN4)				
	-20~50°C (refer to de-rating curve)				
	20~90% RH non-condensing				
	-40~+85°C, 20 90% RH				
Temp. Coefficient	±0.03% (0~50°C)				
	10~500HZ, 2G 10min. / 1cycle period for 60 min. each along X, Y, Z azes				
	Certified EN 6035-1, EN 60335-2-29				
	I/P-O/P: 4242VDC, I/P-FG: 1768VDC, O/P-FG: 700VDC				
	I/P - O/P: 1400M Ohms / 500VDC				
EMC Standards	Certified EN 55022; EN 61204-3; EN 55014-1 Certified EN 61000-3-2, -3-3; EN 61204-3; EN61000-6-3 Certified EN 55024; IEC 61000-4-2, 3, 4, 5, 6, 8, 11;ENV50204; EN 61000-6-1; EN 55014-2				
Others					
Dimension (W×H×D)	183 × 72 × 243 mm	183 × 72 × 243 mm	183 × 72 × 263 mm	213 × 77 × 272 mm	213 × 77 × 312 mm
Packing	1.6kg	1.7kg	1.9kg	3.1kg	4.0kg
NOTE	1. All parameters not specially mentioned are measured at 230VAC input, ratedload and 250°C OF ambient temperature. 2. The charger is considerd a component which will be installed into a final equipment. The final equipmnt must be re-confirmed that it still meets EMC directives. 3. Before charging , make sure the battere charger and battery specificaions are compatible. 4. When using sleep mode, please refer to charging current vs. Ambient temperature de-rating curve. 5. Optional Remote Controller (cr-1).				

یکسو کننده ها ی COTEK و MEAN WELL توسط فن آوری امروز برای شارژ باتری و ضرورت انرژی DC تجهیزات را که با جریان مستقیم تامین طراحی شده است. مناطق استفاده مشترک هستند ارتباط از راه دور، ایستگاه های توزیع انرژی، زمین و وسایل نقلیه حمل و نقل دریایی، پایه صنعتی و نظامی و انواع برنامه شارژ باتری. یکسو کننده ها دارای ساختار کاملا الکترونیکی هستند جریان خروجی و ولتاژ توسط بخش قدرت با تریستور است..